

you can  
**Canon**

**iPF8100 / iPF9100**  
Large Format  
Print Solutions

Ideal for Photography  
and Fine Art

iPF8100 / iPF9100

IDEAL FOR PHOTOGRAPHY AND FINE ART

The imagePROGRAF iPF8100 and iPF9100 are 12-colour pigment ink 44"/60" large format printers delivering jaw-dropping quality, enduring prints, perfect for the Photography and Fine Art Production markets.

Encompassing a twin print head design, the printers deliver:

- Superb quality with 12-colour lightfast pigment inks
- 2,400 x 1,200 dpi reproduction
- Glossy A0 prints in just over 6 minutes
- Smooth colour graduation and scratch resistant prints with reduced graininess and no bronzing.

Built-in colour calibration so no need for external devices.

Continuous performance thanks to ink-tank replacement during printing and selectable high capacity ink tanks 330ml or 700ml.

Borderless printing up to 42" for stunning photographic and fine art prints.



iPF8100

*We Speak Image*

<b>44</b> inch	<b>60</b> inch	<b>2,400</b> x <b>1,200dpi</b>	<b>4</b> pl	<b>12</b> colours	Up to 31.9 sqm/hr plain paper	Up to 9.6 sqm/hr glossy paper	<b>30,720</b> nozzles	Borderless Printing	Built-in Colour Calibration
-------------------	-------------------	--------------------------------------	-------------	----------------------	-------------------------------------	-------------------------------------	--------------------------	------------------------	-----------------------------------

- Automatic Skew Correction, Large LCD and ink level displays for ease-of-use.
- Intuitive software including Digital Photo Front Access and Adobe Photoshop Plug-In.
- Create head-turning posters easily with Canon's PosterArtist tool (optional) offering over 1,000 templates and images.
- 80GB HDD as standard.

Class Ink Type	iPF8100: 44-inch, iPF9100: 60-inch LUCIA Pigment ink, 12 colours (MBK, BK, PC, C, PM, M, Y, R, G, B, GY, PGY)
Maximum Print Resolution	2,400 x 1,200 dpi
Printing Speed (A0 Roll, Full Colour Image)	2:12 (Fast)
Plain paper	4:05 (Standard)
Coated Paper	6:29 (Standard)
Photo Glossy Paper	
Dimensions iPF8100 (W x D x H) (mm)	Main unit with Printer Stand and Basket 1,893 x 975 x 1,144
Weight Packaged	Approx. 142kg
Dimensions W x D x H (mm)	Main unit bundled with Printer Stand and Basket in one package (Palett included), 2,080 x 1,060 x 1,226
Weight Main unit (Palette included)	Approx. 226 kg
Weight Stand and Basket	2,080 x 1,060 x 862 mm; Approx. 175 kg
Weight Packaged	1,795 x 863 x 363 mm; Approx. 43 kg
Dimensions iPF9100 (W x D x H) (mm)	Main unit with Printer Stand and Take-Up Unit 2,299 x 766 x 1,144
Weight Packaged	Approx. 164 kg
Dimensions (W x D x H) (mm)	Main unit and Printer Stand in one package (Palett included) 2,490 x 1,060 x 1,242
Weight Power Supply	Approx. 248 kg
Input power	AC 100 - 240 V (50/60 Hz)
Power consumption Standby power consumption (At the low power mode)	190 W or less 100 V - 120 V - 5 W or less (when IEEE1394 is mounted, 10 W or less)
Power off (standby)	220 V - 240 V - 6 W or less (when IEEE1394 is mounted, 11 W or less) 1 W or less (In compliance with Executive Order of the President of the United States of America)
Operational Environment Temperature	15 - 30°C, Humidity: 10 - 80 % (Condensation free)
Acoustic Noise Acoustic pressure	iPF8100: Operation: 50 dB (A) or less, Standby: 35 dB (A) or less iPF9100: Operation: 51 dB (A) or less, Standby: 35 dB (A) or less
Acoustic power	iPF8100: Operation: 6.6 Bels or less iPF9100: Operation: 6.7 Bels or less
Operation Panel Display Language on operation panel	Large LCD: 160 x 128 dots, Key x 12, LED x 6
Displayable Language on LCD	US-English US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji)
Hard Disk Printer Language	80GB GARO
Interface	Hi-Speed
USB2.0 Type	Built-in
Mode	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer
Connector type Ethernet	Series B (4 pins)
Type Standard	Built-in IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3 x Full Duplex
Protocol	IPX/SPX (Netware 3.2(J)), 4.1 (J), 4.11(J), 4.2(J), 5.0(J), 5.1 (J) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
IEEE1394 (Option) Type Standard	Slot card type IEEE1394 - 1995, P1394a, Half duplex, Data/Strb differential serial 100 / 200 / 400 Mbit/sec.
Data-transfer time	In compliance with IEEE1394 - 1995, 6 pins, No power supply
Connector type	Windows 2000, XP, Server 2003, Vista / Macintosh OS 9, OS X
Operating Systems supported	CE Mark, CB Certification, TUV (GS), Gost-R, UL, FCC class B
Regulations	
<b>PRINT HEAD</b>	
Model	PF-03
Type	Bubble-jet on demand
Head configuration	6 colors integrated type (6 chips per print head x 2 print heads)
Nozzle pitch	1,200 dpi x 2
Nozzle per chip	2,560 nozzles per color
Droplet size	4 pl per color
<b>INK TANK</b>	
Model	PFI-301 (330ml) / PFI-701 (700ml) PC, C, PM, M, Y, R, G, B
Model	PFI-302 (330ml) / PFI-702 (700ml) MBK, BK, GY, PGY

<b>MEDIA HANDLING</b>	
Roll paper	One Roll, Front-loading, Front Output
Cut sheet	Front-loading, Front Output (Manual feed using media locking lever)
Media type	
Roll paper	Standard Paper 80gsm/90gsm, Matt Coated Paper 90gsm/120gsm/140gsm, Extra Matt Coated Paper 180gsm, Opaque Paper 120gsm, High Resolution Graphic Paper - Self Adhesive 140gsm, High Resolution Barrier Paper 180gsm, Glossy Photo Paper 190gsm/240gsm, Satin Photo Paper 190gsm/240gsm, Inst Dry Paper Glossy 200gsm, Inst Dry Paper Satin 200gsm, Photo Paper High Gloss 255gsm, Photo Paper Semi Matt 255gsm, Photo Paper Pearl 260gsm, Photo Realistic Paper 210gsm, Heavy Weight Glossy Photo Paper 300gsm, Heavy Weight Satin Photo Paper 300gsm, Commercial Proofing Paper 200gsm, Commercial RC Proofing Paper 210gsm/270gsm, Glossy Proofing Paper 195gsm, Semi glossy Proofing Paper 195gsm/255gsm, Art Paper Extra Smooth 250gsm, Prem Art Paper Embossed 225gsm, Prem Art Paper Smooth 225gsm, Scrim Banner, Backlit Film, Universal Opaque Film, Roll-Up Film, Water Resistant Art Canvas, Flame-Resistant Cloth, Adhesive Matt Stretch Vinyl.
Media Size	
Roll paper (width)	ISO: A3, A2, A1, A0, JIS: B2, B0, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", 42", 44", iPF9100: 50", 54", 60"
Cut sheet	ISO: A4, A3, A3+, A2, A1, A0, B4, B3, B2, B1, B0, DIN: C4, C3, C2, C1, C0, JIS: B4, B3, B2, B1, B0, ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44", ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48", Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size), Poster: 20 x 30", 30 x 40", 42 x 60", 44 x 62", 300 x 900 mm, Others: 13 x 22" Roll paper & Cut sheet: 0.07 - 0.8 mm
Media Thickness	
Maximum Outside Diameter of Roll Paper	150.0 mm
Media Core Size	Internal diameter of roll core: 2" / 3" (Option)
Media Width	iPF8100: Roll paper: 254 - 1,118 mm Cut sheet: 203.2 - 1,117.6 mm iPF9100: Roll paper: 254 - 1,524 mm Cut sheet: 203.2 - 1,524 mm
Minimal Printable Paper Length	203.2 mm
Maximum Printable Paper Length	Roll paper: 18 m (Varies according to the OS and application)
Cut sheet	1.6 m
Margins (Top, Bottom, Sides)	Roll paper: Top: 20 mm, Bottom: 5 mm, Side: 7 mm Cut sheet: Top: 20 mm, Bottom: 23 mm, Side: 7 mm
Recommended area	Roll paper: Top: 5 mm, Bottom: 5 mm, Side: 5 mm Roll paper (borderless print): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 5 mm, Bottom: 23 mm, Side: 5 mm
Printable area	
Media width for borderless printing	515 mm (JIS B2), 1,030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 16", 24", 36", 42"
<b>OPTION</b>	
Basket, iPF9100	BU-01
Media Take-up Unit, iPF8100	TU-06
Roll Holder Set (2-inch core spindle)	iPF8100, RH2-42 iPF9100, RH2-63
Roll Holder Set (3-inch core spindle)	iPF8100, RH3-42 iPF9100, RH3-63
IEEE1394 Expansion Board	EB-05
Printer stand	iBF8100 ST-43
<b>CONSUMABLES</b>	
Ink Tank	PFI-301 (330 ml), PFI-701 (700 ml); PC, C, PM, M, Y, R, G, B
Ink Tank	PFI-302 (330 ml), PFI-702 (700 ml); MBK, BK, GY, PGY
Print Head	PF-03
Cutter Blade	CT-06
Maintenance Cartridge	MC-08
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



<http://www.imageprograf-printer.co.uk>



Superior print quality only comes with Canon ink and media.

you can  
**Canon**

**Canon Inc.**  
[www.canon.com](http://www.canon.com)

**Canon Europa N.V.**  
[www.canon-europe.com](http://www.canon-europe.com)

English Edition 0119W394  
5026173425162  
© Canon Europa N.V., 2008 (02008)

**Canon (UK) Ltd**  
Woodhatch, Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
[www.canon.co.uk](http://www.canon.co.uk)

**Canon Ireland**  
Arena Road, Sandyford Industrial Estate  
Dublin 18, Ireland  
Telephone No: 01-2052400  
Facsimile No: 01-2958141  
[www.canon.ie](http://www.canon.ie)